CAMBRO

Camshelving® Elements XTRA Series

High Density Storage Top Rail System
High Density Stationary Units
5 Vented, Solid, or VS (4 Vented + 1 Solid)

HEIGHTS	DEPTHS	LENGTHS
1	3	5

81" (2057 mm)	18" (460 mm)	36" (915 mm)
	21" (540 mm)	42" (1070 mm)
	24" (610 mm)	48" (1220 mm)
		54" (1375 mm)
		60" (1525 mm)

- **Top Rail Stationary Starter Unit includes:**
  2 factory assembled stationary post kits, 10 traverses, traverse dovetails, shelf plates, 4 end rail top bolts and 4 floor fasteners. Units ship complete in 1 box.

Features & Benefits

- Trackless, open-floor design offers an alternative for environments where floor tracks may be less practical—such as uneven floors or high-traffic area requiring frequent cleaning. The open space beneath units allows for easy access and simplified maintenance, while still delivering smooth mobility and high-density storage.
- System composed of Top Rail End Kits installed onto Top Rail Stationary Units, joined by Top Rail Middle Kits. Top Rail Mobile Units with top rollers nest securely within the rail system.
- Withstands storage temperatures from -36˚ to 190˚F (-38˚ to 88˚C). Use in walk-in coolers, freezers, dry storage, warewashing areas, loading docks or front of the house. Impervious to moisture, chemicals, salt, food acids, and humidity.
- Posts and traverses are made of revolutionary, extremely strong composite material with a smooth, easy-to-clean surface. Stronger than common wire shelving and lighter in weight than Camshelving Premium Series. Shelf traverse dovetails snap easily and quickly into place.
- Anodized, matte-finish aluminum top rails and type 304 stainless-steel hardware are rust resistant. Top-mounted rollers glide effortlessly, regardless of unit weight or floor surface, for smooth, reliable mobility.
- Removable polypropylene shelf plates have permanent, molded-in Camguard®, an antimicrobial technology that inhibits the growth of mold, fungus and bacteria.
- Shelf traverses can be removed and adjusted easily at 4" (10,2 cm) increments.
- Recommend installing a stationary unit every 15' (4,6 m) of top rail to stabilize the system (must be bolted to the floor).
- Lifetime warranty against rust and corrosion.
- Available in 1 color – Speckled Gray (480).

Project _____

Item No. _____

Model No. _____

Quantity _____



5-Shelf Stationary Unit

camguard
ANTIMICROBIAL SHELF PLATES



Stationary Traverse



Floor Fastener

Weight Bearing Capacity

Weight must be evenly distributed across the entire shelf.

		UNIT LENGTH 36" – 60" (915 - 1525 mm)
STATIONARY UNIT	Unit only	2,400 lbs. (1090 kg)
	Shelf only	800 (365)
	Unit with Dunnage Stand*	2,800 (1270)
	Shelf with Dunnage Stand*	1,200 (545)

* Dunnage Stands add stability and increase weight-bearing capacity on bottom shelf only. Add to any shelf length. Highly recommended for Stationary Units 54" (1375 mm) and longer.

Top Rail End Kits for Stationary Units

CODE	DESCRIPTION	CASE PACK
CSTRSERK18	18" (460 mm) Length Rail for 18" Deep Stationary Unit	1
CSTRSERK21	21" (540 mm) Length Rail for 21" Deep Stationary Unit	1
CSTRSERK24	24" (610 mm) Length Rail for 24" Deep Stationary Unit	1

Color: Silver (000).

- **Top Rail End Kit includes:**
  2 Aluminum rails, 2 end caps, 4 joiners and joiner hardware

Approvals

NSF COMPONENT

Post Connectors, Identification Tags, Security Cages, Peg Board, Shelf Rails, Divider Bars, High Density Rail and Extension Kits are not NSF Listed.

Information and specifications are subject to change without notice. Please confirm at time of order.

© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.

Telephone 714 848 1555 **Toll Free** 800 854 7631 **Customer Service** 800 833 3003 **Email:** customerservice@cambro.com

Printed in USA. REV. 09/25

Camshelving® Elements XTRA Series

High Density Storage Top Rail System
High Density Stationary Units
5 Vented, Solid, or VS (4 Vented + 1 Solid)

Project _____

Item No. _____

Model No. _____

Quantity _____

81" HEIGHT

V5
5-Shelf Vented High Density Stationary Units

	CODE	DIM. D x L x H
18" DEPTH	EST183681V5	18" x 36" x 81" (460 x 915 x 2057 mm)
	EST184281V5	18" x 42" x 81" (460 x 1070 x 2057 mm)
	EST184881V5	18" x 48" x 81" (460 x 1220 x 2057 mm)
	EST185481V5	18" x 54" x 81" (460 x 1375 x 2057 mm)
	EST186081V5	18" x 60" x 81" (460 x 1525 x 2057 mm)
21" DEPTH	EST213681V5	21" x 36" x 81" (540 x 915 x 2057 mm)
	EST214281V5	21" x 42" x 81" (540 x 1070 x 2057 mm)
	EST214881V5	21" x 48" x 81" (540 x 1220 x 2057 mm)
	EST215481V5	21" x 54" x 81" (540 x 1375 x 2057 mm)
	EST216081V5	21" x 60" x 81" (540 x 1525 x 2057 mm)
24" DEPTH	EST243681V5	24" x 36" x 81" (610 x 915 x 2057 mm)
	EST244281V5	24" x 42" x 81" (610 x 1070 x 2057 mm)
	EST244881V5	24" x 48" x 81" (610 x 1220 x 2057 mm)
	EST245481V5	24" x 54" x 81" (610 x 1375 x 2057 mm)
	EST246081V5	24" x 60" x 81" (610 x 1525 x 2057 mm)

Color: Speckled Gray (480).

VS5
5-Shelf, 4 Vented + 1 Solid High Density Stationary Units

	CODE	DIM. D x L x H
18" DEPTH	EST183681VS5	18" x 36" x 81" (460 x 915 x 2057 mm)
	EST184281VS5	18" x 42" x 81" (460 x 1070 x 2057 mm)
	EST184881VS5	18" x 48" x 81" (460 x 1220 x 2057 mm)
	EST185481VS5	18" x 54" x 81" (460 x 1375 x 2057 mm)
	EST186081VS5	18" x 60" x 81" (460 x 1525 x 2057 mm)
21" DEPTH	EST213681VS5	21" x 36" x 81" (540 x 915 x 2057 mm)
	EST214281VS5	21" x 42" x 81" (540 x 1070 x 2057 mm)
	EST214881VS5	21" x 48" x 81" (540 x 1220 x 2057 mm)
	EST215481VS5	21" x 54" x 81" (540 x 1375 x 2057 mm)
	EST216081VS5	21" x 60" x 81" (540 x 1525 x 2057 mm)
24" DEPTH	EST243681VS5	24" x 36" x 81" (610 x 915 x 2057 mm)
	EST244281VS5	24" x 42" x 81" (610 x 1070 x 2057 mm)
	EST244881VS5	24" x 48" x 81" (610 x 1220 x 2057 mm)
	EST245481VS5	24" x 54" x 81" (610 x 1375 x 2057 mm)
	EST246081VS5	24" x 60" x 81" (610 x 1525 x 2057 mm)

Color: Speckled Gray (480).

S5
5-Shelf Solid High Density Stationary Units

	CODE	DIM. D x L x H
18" DEPTH	EST183681S5	18" x 36" x 81" (460 x 915 x 2057 mm)
	EST184281S5	18" x 42" x 81" (460 x 1070 x 2057 mm)
	EST184881S5	18" x 48" x 81" (460 x 1220 x 2057 mm)
	EST185481S5	18" x 54" x 81" (460 x 1375 x 2057 mm)
	EST186081S5	18" x 60" x 81" (460 x 1525 x 2057 mm)
21" DEPTH	EST213681S5	21" x 36" x 81" (540 x 915 x 2057 mm)
	EST214281S5	21" x 42" x 81" (540 x 1070 x 2057 mm)
	EST214881S5	21" x 48" x 81" (540 x 1220 x 2057 mm)
	EST215481S5	21" x 54" x 81" (540 x 1375 x 2057 mm)
	EST216081S5	21" x 60" x 81" (540 x 1525 x 2057 mm)
24" DEPTH	EST243681S5	24" x 36" x 81" (610 x 915 x 2057 mm)
	EST244281S5	24" x 42" x 81" (610 x 1070 x 2057 mm)
	EST244881S5	24" x 48" x 81" (610 x 1220 x 2057 mm)
	EST245481S5	24" x 54" x 81" (610 x 1375 x 2057 mm)
	EST246081S5	24" x 60" x 81" (610 x 1525 x 2057 mm)

Color: Speckled Gray (480).

Optional Accessories

- ❑ Shelf Identification Tags
- ❑ Shelf Divider Panel
- ❑ Shelf Divider Bars (Straight or Angled)
- ❑ Shelf Rails
- ❑ Wall Fastener
- ❑ Single Shelf Sheet Pan/Tray Rack
- ❑ Single Shelf Security Cage
- ❑ Shelf Traverses (Single or Double)
- ❑ Bottom Shelf Dunnage Stands
- ❑ Single and Add-on Can Racks

Architect Specs

Posts and Traverses: Proprietary non-corrosive composite material.
Post Connectors: Reinforced polypropylene.
Shelf Plates: Reinforced polypropylene with Camguard® antimicrobial.
Floor Fasteners: Type 304 Stainless Steel.
Traverse Dovetails: Reinforced nylon.
Post Connector Collar Wedges: Reinforced nylon.

Approvals

NSF COMPONENT

Post Connectors, Identification Tags, Security Cages, Peg Board, Shelf Rails, Divider Bars, High Density Rail and Extension Kits are not NSF Listed.

CAMBRO®

www.cambro.com

Information and specifications are subject to change without notice. Please confirm at time of order.
© Cambro Manufacturing Company 5801 Skylab Road, Huntington Beach, California 92647-2056, U.S.A.
Telephone 714 848 1555 **Toll Free** 800 854 7631 **Customer Service** 800 833 3003 **Email:** customerservice@cambro.com
Printed in USA. REV. 09/25

EXTRS5

D092501