

NH2 (Sanitation Service Entrance) Series


Unheated
Model Lengths: 36”–144”
Insect Control (up to 7’)

atmosphere is everything
14716 S. BROADWAY, GARDENA, CA 90248 ● Ph: (310)532-1555 ● Fax: (310)-532-3030 ● www.marsair.com
© Copyright Mars Air Systems, LLC 2014




TOP VIEW


FRONT VIEW



SIDE VIEW



REAR VIEW

Notes:

1. Internal junction boxes provided for electrical wiring: (1) 2”x4” box for one-motor units, (1) 4”x4” box for two-motor units, (2) 4”x4” box for three-motor units.
2. Recommended service clearances are 2” to the left and right sides, 6” on top, and 18” in front of the unit.
3. Circuit protection (per NEC) to be installed by others.
4. To prevent accidental damage during operation, unit must be installed so that the bottom of the air curtain does not extend below the door header.
5. Unit can be fastened to wall on both ends without intermediate support.
6. Motor-Fan Assemblies (MFAs) are shipped loose to minimize freight damage.

Model Number	Mechanical Data						AMCA Certified Lab Data (at Discharge Nozzle)				
	Overall Length A (in)	Nozzle Length (in)	Top Knockout Location B (in)	Rear Knockout Location C (in)	Motor (hp)	Weight (lb)	Max Core Velocity at Nozzle (fpm)	Avg Velocity (fpm)	Volume (cfm)	Uniformity (%)	Power Rating (watt)
☐ NH236-1U*-TS	36	36	10 ½	21 ½	1	115	6000	2745	2059	90	1245
☐ NH242-1U*-TS	42	42	13 ½	24 ½	1	120	6051	2654	2322	93	1305
☐ NH248-1U*-TS	48	48	16 ½	27 ½	1	125	6144	2447	2447	88	1360
☐ NH272-2U*-TS	72	72	31 ½	40 ½	(2) 1	220	6000	2745	4118	90	2490
☐ NH284-2U*-TS	84	84	37 ½	46 ½	(2) 1	235	6051	2654	4644	93	2610
☐ NH296-2U*-TS	96	96	43 ½	52 ½	(2) 1	250	6144	2447	4894	88	2720
☐ NH2108-3U*-TS	108	108	31 ½	40 ½	(3) 1	330	6000	2745	6177	90	3735
☐ NH2120-3U*-TS	120	120	35 ½	44 ½	(3) 1	345	6060	2677	6693	93	3615
☐ NH2144-3U*-TS	144	144	43 ½	52 ½	(3) 1	375	6144	2447	7341	88	4080
The following model is not licensed to bear the AMCA seal											
☐ NH260-2U*-TS	60	60	22 ½	33 ½	(2) 1	195	6025	3036	3795	93	2301

*** – Use corresponding letters in “Electrical Data” column headers (see page 2) to complete the model numbers.**

Note: above data is for 60 Hz at 1725 RPM. For 50 Hz, RPM is 1425 with a 17% reduction in performance. Units may not comply with ANSI/NSF 37 minimum airspeed requirements at 50 Hz.

- *The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection, and power rating at free delivery only.*
- *Complies with ANSI/NSF 37 standards by generating a minimum 1600 fpm air velocity 3’ above floor when mounted at 7' above floor.*

NOTE: Mars Air Systems, LLC reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions, or replacements for previously purchased equipment.

NH2 (Sanitation Service Entrance) Series

Unheated
Model Lengths: 36”–144”
Insect Control (up to 7’)

atmosphere is everything

14716 S. BROADWAY, GARDENA, CA 90248 ● Ph: (310)532-1555 ● Fax: (310)-532-3030 ● www.marsair.com
© Copyright Mars Air Systems, LLC 2014

Standard Features:

- ETL-certified to conform to ANSI/NSF 37 Standards for service entrances up to 7’
  - Generates a minimum 1600 fpm air velocity at 3' from the floor
- ETL-certified to conform to UL 507 (US) and CSA 22.2 (Canada) standards for indoor/outdoor use
- AMCA-certified to AMCA 211 (includes performance testing per AMCA 220)
  - Certified models are approved for use as alternate to vestibules (per ASHRAE 90.1, IECC, and IgCC)
- Sleek self-contained one-piece heavy-gauge corrosion-proof paint lock metal design
- Fire retardant and rust preventative electrostatic polyurethane powder coating
  - Standard color is Titanium Silver (TS)
- 1 HP continuous duty Totally Enclosed Air Over (TEAO) motors (NEMA 1)
- Adjustable air directional vanes with 40° sweep front to back
- 5-year parts warranty
- Freight included (FOB continental USA)
- Proudly made in the USA

Electrical Data Full Load Amp (FLA)	Unit Amperage (Voltage Code)				
	Single Phase		Three Phase		
	115V/1Ø ☐ (A)	208-230V/1Ø ☐ (D)	208-230V/3Ø ☐ (G)	460V/3Ø ☐ (H)	575V/3Ø ☐ (I)
☐ NH236-1U*-TS	9.0	5.0	3.3/3.2	1.6	1.3
☐ NH242-1U*-TS	9.0	5.0	3.3/3.2	1.6	1.3
☐ NH248-1U*-TS	9.0	5.0	3.3/3.2	1.6	1.3
☐ NH260-2U*-TS	18.0	10.0	6.6/6.4	3.2	2.6
☐ NH272-2U*-TS	18.0	10.0	6.6/6.4	3.2	2.6
☐ NH284-2U*-TS	18.0	10.0	6.6/6.4	3.2	2.6
☐ NH296-2U*-TS	18.0	10.0	6.6/6.4	3.2	2.6
☐ NH2108-3U*-TS	27.0	15.0	9.9/9.6	4.8	3.9
☐ NH2120-3U*-TS	27.0	15.0	9.9/9.6	4.8	3.9
☐ NH2144-3U*-TS	27.0	15.0	9.9/9.6	4.8	3.9

* – Use corresponding letters in “Voltage Code” column headers to complete the model numbers.

Ampacity (MCA) = total FLA x 1.25

Alternate voltage codes with FLA data:
·277V/1Ø/60Hz (L) – 5.2A per motor
·220V/1Ø/50Hz (U) – 7.1A per motor
·380-415V/3Ø/50Hz (W) – 1.8A per motor

Washdown motor FLA data (INS-WD-STD2):
·115V/1Ø/60Hz (A) – 12A per motor
·208-230V/1Ø/60Hz (D) – 6.4/6A per motor
·208-230V/3Ø/60Hz (G) – 3.3A per motor
·460V/3Ø/60Hz (H) – 1.5A per motor

Mars Recommended Accessories (see catalog for complete listing):

- Door Limit Switches (§)
  - ☐ 99-014, Combination mechanical switch, 250V, 1HP Max
  - ☐ 99-125, Industrial surface mounted magnetic switch (controller required)
- Controllers
  - ☐ MCPB-†U*, Motor Control Panel, 120V control voltage († = # of Motors, * = Voltage Code) (§)
  - ☐ MCP-TD, Adjustable time delay, 1sec-100hr (panel required)
  - ☐ MCP-24V, Low voltage control option (panel required)
  - ☐ BMS-303, BMS for monitor and control (panel with MCP-24V required)


    Note: *Dry contact provided in panel for monitoring motor. 24Vac signal provided from panel for controlling motor.*
- Brackets (§)
  - ☐ B0004, Adjustable mounting bracket set, 3½” clearance
  - ☐ B0008 to B0011, Extended wall mounting bracket set, 10”, 16”, 19”, and 23” clearance respectively
- Severe Duty and Finish
  - ☐ HSG-304SS-HV/EP, 304 Stainless steel housing construction
  - ☐ INS-WD-HV2, Washdown motor fan assembly, IP54

    Note: *Washdown units draw higher motor amperage (see electrical data table). Control panels for these units require OL/MP with higher amperage range (use MCP-MWD accessory).*

(§) = Shipped loose

AMCA Certified Projection Velocity		
Model	Distance from Nozzle (in)	Average Core Velocity (fpm)
NH236-1U*	40	2002
	80	1238
	120	1088
	160	1039
	200	967

EXAMPLE



Sound Levels (measured at 10’ in a free field):

1 Motor Unit = 70 dBA, 2 Motor Unit = 73 dBA, 3 Motor Unit = 75 dBA

MARS Air Systems, LLC certifies that the Air Curtains shown on this data sheet are licensed to bear the AMCA seal. The ratings shown are based on tests and procedures performed in accordance with AMCA Publication 211 and comply with the requirements of the AMCA Certified Ratings Program.
The AMCA Certified Ratings Seal applies to airflow rate, average outlet velocity, outlet velocity uniformity, velocity projection and power rating at free delivery only.

Intertek Intertek

NOTE: Mars Air Systems, LLC reserves the right to change specifications and product design without notice. Such revisions do not entitle the buyer to corresponding changes, improvements, additions, or replacements for previously purchased equipment.